

POLYETHYLENE DISPERSION

**HIGH FLAT 1459**

Featuring : HIGH FLAT 1459 is the dispersion of low molecular weight polyethylene in Xylene.  
HIGH FLAT 1459 is the best additives to paints and other coatings with soft flattening agent.  
HIGH FLAT 1459 give your finishes the best qualities in slipping agent, anti-blocking agent and mar proof agent.

Appearance : Milky white dispersion

Typical properties : Wax content (%)	15.0
G.M. ( $\mu$ m)	10~13

Remarks : 1. Store at 0 °C ~ 35 °C  
Keep away from the place in sunshine and heat generator (pyrogen)

2. Use up quickly at opening.  
The remnant is a factor of small numerous lumps with secondary cohesion from evaporation of solvent at product adhered inner surface.

3. Avoid heating and cooling.  
If not so, it's dispersoid will be changing and it's viscosity will be rising.  
Please avoid the generation of heat by high-speed mixing.

4. Shake the vessel at using.  
Please confirm the fluidity. In cold storage (ex. winter), the product will be gelation temporarily.

5. Handle with care to ventilation and safeguard to avoid poisoning from inhalation of toluene and esters.

Packing : Net 15 kgs in 18 litre steel JERRI CAN.  
170 kgs in 200 litre steel drum.